

NBS SPECIFICATION – ‘SOLUS’ TYPE WA ROOFLIGHTS

MANUFACTURER:	Lareine Engineering Ltd, Unit 1, Armadale Industrial Estate Armadale, West Lothian, EH48 2ND E Mail: info@lareineengineering.com Website: www.lareineengineering.co.uk Tel: 01501 731600/ 731699 Fax: 01501 733828
PRODUCT REFERENCE:	‘Solus’ Type WA Rooflight
TYPE:	Rooflights suitable for new or existing upstands.
FRAME:	Aluminium, aluminium to BS 1474:1987 Alloy 6063-T6. AA Fire rated to surface spread of flame to BS 476: Part 7: 1997.
FINISH:	Mill Finish or any Standard RAL colour – painted white internally. Polyester powder coated to BS EN 12206:2004 Part 1 Interpon D1036. Standard RAL colour.
GLAZING:	3mm UV coated polycarbonate inner skin, 3mm or 4mm UV coated polycarbonate outer. The glazing is Makrolon Mono Longlife UV resistant polycarbonate sheet. 10 Year warranty on breakage, excessive yellowing and loss of light transmission. Fire Rating: Makrolon 2099 when tested to BS 476 Part 3 is rated AA surface spread of flame to BS 476 Part 7 Class 1. Class O material to Building Regulation 1985. TP (a) rigid classification as described in approved Document B of Building Regulation 1991.
FRAGILITY:	They have been tested and are classed as NON-FRAGILE Class B to ACR (M) 001:2014 Test for non-fragility of profiled sheeted and large element roofing assemblies. (Fifth edition)
TESTED/MANUFACTURED TO:	All Rooflights are tested and manufactured & certificated to: BS EN 6375 Weather Tightness BS EN 1026 Air Permeability BS EN 1027 Water Tightness of Glass Rooflights BS EN 1873 Water Tightness of Polycarbonate Rooflights
‘U’ VALUE	Double skin 2.7 W/m ² K, Triple skin 1.35 W/m ² K
PROFILE:	Dome or Pyramid.
LIGHT TRANSMISSION:	Clear – 90% Opal – 50% (other options available)
SIZES:	To suit your requirements.
FIXING:	In accordance with Lareine Engineering fixing recommendations.